

AMD Linux Driver 2022.30 Release Notes

© 2022 Advanced Micro Devices, Inc. All rights reserved.

The information contained herein is for informational purposes only, and is subject to change without notice. While every precaution has been taken in the preparation of this document, it may contain technical inaccuracies, omissions and typographical errors, and AMD is under no obligation to update or otherwise correct this information. Advanced Micro Devices, Inc. makes no representations or warranties with respect to the accuracy or completeness of the contents of this document, and assumes no liability of any kind, including the implied warranties of noninfringement, merchantability or fitness for particular purposes, with respect to the operation or use of AMD hardware, software or other products described herein. No license, including implied or arising by estoppel, to any intellectual property rights is granted by this document. Terms and limitations applicable to the purchase or use of AMD's products are as set forth in a signed agreement between the parties or in AMD's Standard Terms and Conditions of Sale. Any unauthorized copying, alteration, distribution, transmission, performance, display or other use of this material is prohibited.

Trademarks

AMD, the AMD Arrow logo, AMD AllDay, AMD Virtualization, AMD-V, PowerPlay, Vari-Bright, and combinations thereof are trademarks of Advanced Micro Devices, Inc. Other product names used in this publication are for identification purposes only and may be trademarks of their respective companies.

Dolby is a trademark of Dolby Laboratories.

HDMI is a trademark of HDMI Licensing, LLC.

HyperTransport is a licensed trademark of the HyperTransport Technology Consortium.

Microsoft, Windows, Windows Vista, and DirectX are registered trademarks of Microsoft Corporation in the US and/or other countries.

MMX is a trademark of Intel Corporation.

OpenCL is a trademark of Apple Inc. used by permission by Khronos.

PCIe is a registered trademark of PCI-Special Interest Group (PCI-SIG).

USB Type-C[®] and USB-C[®] are registered trademarks of USB Implementers Forum.

Reverse engineering or disassembly is prohibited.

USE OF THIS PRODUCT IN ANY MANNER THAT COMPLIES WITH THE MPEG ACTUAL OR DE FACTO VIDEO AND/OR AUDIO STANDARDS IS EXPRESSLY PROHIBITED WITHOUT ALL NECESSARY LICENSES UNDER APPLICABLE PATENTS. SUCH LICENSES MAY BE ACQUIRED FROM VARIOUS THIRD PARTIES INCLUDING, BUT NOT LIMITED TO, IN THE MPEG PATENT PORTFOLIO, WHICH LICENSE IS AVAILABLE FROM MPEG LA, L.L.C., 6312 S. FIDDLERS GREEN CIRCLE, SUITE 400E, GREENWOOD VILLAGE, COLORADO 80111.

Chapter 1 Overview

AMD's Linux® Driver's includes open source graphics driver for AMD's embedded platforms and other peripheral devices on selected development platforms.

New features supported in this release:

- Main line kernel 5.18 stable support.
- Bug fixes.

Chapter 2 Linux® Kernel Support

- 5.18.0 stable

Chapter 3 Linux Distribution Support

- Ubuntu 22.04

Chapter 4 Component Versions

The following table shows git commit details of the sources and binaries used in the package.

The patches present in patches folder of this release package has to be applied on top of the git commit mentioned in the below table to get the full sources corresponding to this driver release. The sources directory in this package contains patches pre-applied to these commit ids.

AMD Linux Driver 2022.30 Release Notes

Component Name	Version	Commit ID	Source Link for git clone
Kernel	5.18-stable	4b0986a3613c92f4ec1bdc7f60ec66fea135991f	https://github.com/torvalds/linux/tree/v5.18
Libdrm	2.4.112	60cf6bcef1390473419df14e3214da149dbd8f99	https://github.com/freedesktop/ mesa-drm.git
Mesa	22.1.1	7a3414c4bd1720057cb84fdd1c033e87bf9c996d	https://github.com/mesa3d/mesa.git
Ddx	21.1.0	533bd30ceaa373788b3d0bfd4d486f0f1c624d0c	https://github.com/freedesktop/xorg-xf86-video-amdgpu.git
Gstomx	1.0.0.1	5c4bff4a433dff1c5d005edfcef727b6214bb74	git://people.freedesktop.org/~leoliu/gstomx
Wayland	1.20.93	8e322a5a99db1cefb7494f082a5525d2cba64174	https://github.com/wayland-project/wayland
libva	2.15.0	b095d10bf355110352e75c22e581018a7ea7de5a	https://github.com/intel/libva.git
libvdpau	1.1.1	af517f56d64118520aa0c8456318dd9ec3307e94	https://github.com/freedesktop/libvdpau.git
LLVM	14.0	f28c006a5895fc0e329fe15fead81e37457cb1d1	https://github.com/llvm/llvm-project
Firmware	Master	8413c63c7a539a912be8851ce941eea32dcd1786	https://git.kernel.org/pub/scm/linux/kernel/git/firmware/linux-firmware.git
Vulkan	refs/tags/v-2022.Q3.3	a6732d132aaeabc9845ba3ca20f1740c56805b9e	https://github.com/GPUOpen-Drivers/AMDVLK/tree/v-2022.Q3.3
Supported Applications			
LunarG Vulkan SDK	1.2.182	NA	https://vulkan.lunarg.com/sdk/home#linux
Vulkan CTS	1.2.2.2		https://github.com/KhronosGroup/Vulkan-CTS.git
RGP	1.10	NA	https://github.com/GPUOpen-Tools/radeon_gpu_profiler/tree/v1.10

Chapter 5 Features Supported on APU

Supported features are shown in the following table.

Feature Group	Feature Supported	V1000	R1000/LP	R1600	V2000	V1500P/B	R2000
2D	2D acceleration	Yes	Yes	NA	Yes	NA	Yes
3D	EGL 1.4, 1.5, EGL extensions.	Yes	Yes	NA	Yes	NA	Yes
3D	OGL 4.5, OGL 4.6	Yes	Yes	NA	Yes	NA	Yes
3D	GLX 1.4	Yes	Yes	NA	Yes	NA	Yes
3D	DRI3 support	Yes	Yes	NA	Yes	NA	Yes
3D	DRI3 updates (VDPAU, VAAPI)	Yes	Yes	NA	Yes	NA	Yes
3D	Vulkan Open Source	Yes	Yes	NA	Yes	NA	Yes
2D	10 bit Display	Yes	Yes	NA	Yes	NA	No
Audio	DP Audio supports for standard	Yes	Yes	NA	Yes	NA	Yes
Audio	I2S Audio	Yes	Yes	NA	Yes	NA	Yes
Display	EDID(Basic)	Yes	Yes	NA	Yes	NA	Yes
Display support	X and Desktop support	Yes	Yes	NA	Yes	NA	Yes
Display support	Tear Free Desktop	Yes	Yes	NA	Yes	NA	Yes
Display support	Partial support RandR 1.4 capabilities	Yes	Yes	NA	Yes	NA	Yes
Display support	Kernel Mode Setting	Yes	Yes	NA	Yes	NA	Yes
Display support	4K60HZ display support	Yes	Yes	NA	Yes	NA	Yes
Display support	Multi-GPU support (Refer table below for dGPU pairing)	Yes	No	NA	No	NA	No
Display support	No of Displays supported (Refer display support table below)	-	-	NA	-	NA	-
Display support	4K cinema	Yes	Yes	NA	Yes	NA	No
Display support	DP MST	Yes	Yes	NA	Yes	NA	Yes
Display Support	Single Large Surface (SLS)	Yes	Yes	NA	Yes	NA	No
Play back	Play back support MPV player using VAAPI / VDPAU	Yes	Yes	NA	Yes	NA	Yes
Play back	Play back support for Gstreamer using VAAPI, gstomx (not recommended)	Yes	Yes	NA	Yes	NA	Yes

AMD Linux Driver 2022.30 Release Notes

Feature Group	Feature Supported	V1000	R1000/LP	R1600	V2000	V1500P/B	R2000
Play back	1080p 24fps, 30 fps and 60fps video play back	Yes	Yes	NA	Yes	NA	Yes
Play back	4k 30fps video play back	Yes	Yes	NA	Yes	NA	Yes
Play back	4k 60fps video play back	Yes	Yes	NA	Yes	NA	Yes
Power Management	Power Play support to re-clock	Yes	Yes	NA	Yes	NA	Yes
	initial GPU reset support	Yes	Yes	NA	Yes	NA	Yes
	Power Play sysfs interface for manually selecting clock speeds	Yes	Yes	NA	Yes	NA	Yes
	S3	Yes	Yes	NA	Yes	Yes	Yes
	S5	Yes	Yes	NA	Yes	Yes	Yes
VDPAU Post Processing	Deinterlace	Yes	Yes	NA	Yes	NA	Yes
VDPAU Post Processing	Edge Enhancement	Yes	Yes No (LP)	NA	Yes	NA	Yes
VAAPI Postprocessing	Deinterlace	Yes	Yes No (LP)	NA	Yes	NA	Yes
Transcode	4k Encode	Yes	Yes No (LP)	NA	Yes	NA	Yes
Video Quality	Scaling and color space conversion (CSC)	Yes	Yes	NA	Yes	NA	Yes
Video Quality	Pull down detection and Deinterlacing	Yes	Yes	NA	Yes	NA	Yes
Video Quality	Support for software scaling	Yes	Yes	NA	Yes	NA	Yes
Video Quality	Support for hardware scaling	No	No	NA	No	NA	Yes
Video Quality	10-bit Decode with 10 bit render	NA	NA	NA	NA	NA	Yes
Compute	OpenCL	NA	NA	NA	NA	NA	No
dGMA –OpenGL		Yes*	Yes	NA	Yes	NA	NA
dGMA - OpenCL		Yes (V1000 NPU also)	Yes	Yes	No	NA	NA
fTPM		Yes* (V1000 NPU also)	Yes	Yes	No	Yes*	Yes
RJ45	1G	Yes* (V1000 NPU also)	Yes	Yes	No	Yes	No
	2.5G	Yes* (V1000 NPU also)	Yes	Yes	No	Yes	No
	10G	Yes (V1000 NPU also)	Yes	Yes	No	Yes*	No

AMD Linux Driver 2022.30 Release Notes

Feature Group	Feature Supported	V1000	R1000/LP	R1600	V2000	V1500P/B	R2000
SFP+ (connector)	1G	Yes (V1000 NPU also)	Yes	Yes	No	Yes*	No
	10G	Yes (V1000 NPU also)	Yes	Yes	No	Yes*	No
eMMC	BC	Yes (V1000 NPU also)	Yes	Yes	No	No	Yes
	HS200	Yes (V1000 NPU also)	Yes	Yes	No	No	Yes
	HS400	Yes (V1000 NPU also)	Yes	Yes	No	No	Yes
SD Card	SD UHS I – SDR50	Yes (V1000 NPU also)	Yes	Yes	Yes	Yes	Yes
	SD UHS I – SDR104	Yes	Yes	Yes	Yes	Yes	Yes
	SD UHS I – SDR104	Yes	Yes	Yes	Yes	Yes	Yes
Peripherals (I/O)	I2C	Yes	Yes	Yes	Yes	Yes	Yes
	USB	Yes	Yes	Yes	Yes	Yes	Yes
	SATA	Yes	Yes	Yes	Yes	Yes	Yes
	UART	Yes	Yes	Yes	Yes	Yes	Yes
	WDT	Yes	Yes	Yes	Yes	Yes	Yes
	SMBUS	Yes	Yes	Yes	Yes	Yes	Yes
	SPI Kernel Driver *	Yes	Yes	Yes	Yes	Yes	Yes

*Bilby platform only

*To use the SPI kernel driver on Bilby platforms, the BIOS which has enabled SPI Entry in the ACPI table is required. The default BIOS does not have this feature. Please contact your FAE for the required BIOS.

Chapter 6 Features Supported on DGPU:

The 2022.20 Linux driver is not supported any AMD Embedded dGPUs.

6.1 Display Support:

Platform	No of display(s)	
R2000	R2312	3
	R2314	
	R2514	
	R2544	4
V2000	4	
R1000 LP	R1102G(B2): 1x4k@60HZ or 2x1080@60HZ	
	R1305G(B4): 2x4k@60HZ or 3x1080@60HZ	
R1000	3	
V1000	4	

6.2 HW Codec Support

Codec	API	Middleware/Framework
H.264 decode	VAAPI, VDPAU, OMX	ffmpeg-VAAPI, ffmpeg-VDPAU, gst-VAAPI, gst-OMX
H.265 decode	VAAPI, VDPAU, OMX	ffmpeg-VAAPI, ffmpeg-VDPAU, gst-VAAPI, gst-OMX
H.265 10bit->8bit decode (PF & V1000 only)	VAAPI	ffmpeg-VAAPI
MPEG2 decode	VAAPI, VDPAU, OMX	ffmpeg-VAAPI, ffmpeg-VDPAU, gst-VAAPI, gst-OMX
MPEG4 Part2 decode	VDPAU	ffmpeg-VDPAU
VC1 decode	VAAPI, VDPAU	ffmpeg-VAAPI, ffmpeg-VDPAU, gst-VAAPI
H.264 encode	VAAPI, OMX	gst-VAAPI, gst-OMX,
VP9 decode	VAAPI	Ffmpeg-VAAPI

Chapter 7 Platforms Supported

- R2000 (R2314/R2312/ R2514/ R2544)
- V1500P/V1500B
- V2000
- R1600 CPU
- R1000LP
- R1000
- V1000
- V1000 NPU

Chapter 8 Tested Platform Configurations

The following tables show the system configuration that was used for testing the driver package.

R2000	
APU	R2000
OPN's	R2312, R2314, R2544, R2514
APU TDP	12-25W, 12-35W
BIOS version	RBP1001A
VRAM setting	4GB
RAM	16GB
Display Convertors / Dongles Used	DP to HDMI, HDMI
Storage disk	SSD, M.2

V2000	
APU	V2000
APU TDP	10-25W, 35-54W
BIOS version	RC01006A
VRAM setting	4GB
RAM	16GB
Display Convertors / Dongles Used	DP to HDMI, HDMI
Storage disk	SSD, M.2

R1000 LP	
APU	R1000 LP
APU Frequency	B2 6W, B4 8W/10W
BIOS version	RBB1208A
VRAM setting	4GB
RAM	16GB
Display Convertors / Dongles Used	DP to HDMI, HDMI
Storage disk	HDD, SSD, M.2

R1000	
APU	R1000
APU Frequency	B2 15W, B4 15W/25W
BIOS version	RBB1208A
VRAM setting	4GB
RAM	16GB
Display Convertors / Dongles Used	DP to HDMI, HDMI
Storage disk	HDD, SSD, M.2

V1000/NPU	
APU	V1000
APU Frequency	B10 45W (3350 MHz), B8 45W(3250 MHz), B8 15W(2000 MHz), B3 15W(2000 MHz)
BIOS version	RBB1208A
VRAM setting	4GB
RAM	16GB
Display Convertors / Dongles Used	DP to HDMI, DP to VGA, DP to DVI, mDP
Storage disk	HDD, SSD, M.2

V1500	
CPU	V1500
OPNs	V1500P and V1500B
TDP	16W/25W
BIOS version	RBB1208A_RV_PCO
RAM	16GB (2x8GB DDR4 2400)
Storage disk	M.2 SATA

Chapter 9 Issues Fixed

- No issues fixed in this release

Chapter 10 Known Issues/Limitations

R2000 Issues:

1. Stutter observed for video playback through chromium browser.
2. Glitches observed with zoom calls on 3x4k/1080p display configuration.
3. Lag observed with teams video conference, PPT, browser on 3x4k display configuration.
4. Stutter and lag observed with 4k videoplay back with thin client config.
5. Stutter observed at times on secondary displays with 3x4k config.
6. One of the display goes blank after boot with 3xTrue 2K MST configuration.
7. Sporadically Type C to Type C Hot plug fails.
8. Minor stutter observed at times with vaapi playback with MST-4K@30hz.

V2000 Issues:

1. Randomly blank-out observed during S3 cycles with 4X4K_HDMI@60hz configuration on LG27UK650.
2. 4k@120 Hz refresh rate is not working with HDMI.
3. Keyboard and Mouse is not responsive with ACCELL make TYPIC to HDMI Active dongle on USB-C-P0 port.
4. Minor stutter observed at times with vaapi playback with MST-4K@30hz.

V1500B Issues:

1. AVT Application crash observed while starting Thermal/Memory/P-states.
2. Less throughput values observed with 1T (1 Thread) Uni and Bi directional using 100M RJ45 peer-to-peer connection.
3. Observed Flow control is disabled in one of the peer to peer config.
4. As BIOS does not have option currently to set 100M speed, ethtool needs to be used to set 100M on SUT from Linux driver.

R1000 LP Issues:

1. Heavy stutter in slideshow presentation and Multimedia playback in dual monitor usecase.
 - i. Note: Issue is happening due to hitting the power limit with the above use case.
2. Minor Tearing is observed while doing skype video calling in fullscreen.
3. Tearing and stutter observed in Multimedia playback of H265 1080p@60fps in dual monitor scenario along with PPT presentation in one monitor.

R1000 Issues:

1. Not showing GPU Load in amdgpu_pm_info sysfs entry on V1000 and R1000/LP.
2. User experience is very poor after hotplug on mGPU config with more than 6 monitors.

Common Issues:

1. Few of the display blank out with MST hub in 5.4 kernel.
2. Few of the VulkanCTS 1.2 test cases fails with error of `VK_ERROR_OUT_OF_HOST_MEMORY`.
[Workaround]: Vulkan CTS 1.1.3 works fine.
3. IO Page fault logs observed while loading the I2S module.
4. HP Z27s monitor resolution change does not take effect sometimes.
Recommendation: Not to use the monitor since the monitor issues HPD pulse during Changing resolution causing to revert to previous/native resolution sometimes.
5. Hotplug root node of DP MST monitors in daisy chain or via Hub fails.
Workaround: To always connect or disconnect monitors in MST configuration one by one and not at root node level.
6. All MST displays goes blank while booting with MST Hub and MST off on the monitors.
7. Tearing/Stutter observed during 4k@60fps playback on 2x4k monitors.
Workaround: Use zaphord Head configuration to play 4k@60fps video on multi monitor setup.
8. Hard hang observed for Piglit tests.
Workaround: Piglit test passed without `arb_tessellation_shader-tes-gs-max-output` test cases.
9. Stuttering observed with glmark2 on mGPU config.
Workaround: Use multi screen configuration to resolve the stutter.
10. [BE]: Observed Issues with HotPlug on Bald Eagle.
11. [BE]: S3 Fails randomly on BaldEagle with IOMMU enabled.
12. Issues with refresh rate change/rotate using `xrandr` command.
13. Export `MESA_GLES_VERSION_OVERRIDE=3.2` to run OGL ES 3.2 CTS.
14. Hot plug results in blank display of one of the monitors when using startx mode.
15. B-frame support is not available in vaapi encode.
16. MF has limitation of displaying 2 – 4K monitors, 3rd 4 K monitor will not get displayed.
17. Following OGL CTS test cases do not work
 - a. GL45-CTS.stencil_texturing.functional
 - b. GL45-CTS.multi_bind.dispatch_bind_textures
 - c. GL45-CTS.multi_bind.dispatch_bind_image_textures
 - d. GL45-CTS.arrays_of_arrays_gl.SubroutineFunctionCalls2
 - e. GL45-CTS.sparse_buffer_tests.BufferStorageTest

- f. GL45-CTS.shader_atomic_counters.basic-usage-fs
- g. GL45-CTS.shader_atomic_counters.basic-usage-vs
- h. GL45-CTS.shader_atomic_counters.basic-usage-gs
- i. GL45-CTS.shader_atomic_counters.basic-usage-tes
- j. GL45-CTS.shader_atomic_counters.basic-usage-cs
- k. GL45-CTS.parallel_shader_compile.CompilationCompletionNonParallelTest
- l. GL45-CTS.parallel_shader_compile.CompilationCompletionParallelTest
- m. GL45-CTS.enhanced_layouts.ssb_member_offset_and_align
- n. GL45-CTS.enhanced_layouts.vertex_attr_locations
- o. GL45-CTS.parallel_shader_compile.MaxShaderCompileThreadsTest

XGBE:

1. 10G SFP Hot plug(FC) is not working.
2. [XGBE]: Force mode(Auto negotiation disabled) is not supported in RJ45.
3. Sporadically 2.5G Network is established after a delay of more than 20 sec for SFP 2.5 on Port 0/1.
4. 10G SFP Hot plug(FC) is not working with NetGear switch(XS724EM model)
5. Can't concurrently enable SFP+ and RJ45 interfaces.
6. No IEEE 1588 Timestamp support.
7. No receive Split header support.
8. Following features should be functional but have not been fully validated: Priority and VLAN (VLAN Priority Control), RMON Counter, VLAN support and Receive-Side scaling, 2.5G TCP/IP offload (duplex) and 2.5G jumbo frames (duplex).

Below is the type of SFP/RJ45 modules used in the XGBE validation of this release.

Type	Model	Part Number
1G SFP - RJ45	BEL	SFP-1GBT-06
1G SFP - RJ45	Finisar	FCLF8521P2BTL
10G SFP+ passive direct cable	Finisar	F17CC004893
10G SFP optical	Finisar	FTLX8574D3BCL
10G SFP optical	Finisar	FTLX851D3BCL
10G SFP optical	Intel	E10G42BTDABLK
10G SFP optical	Intel	AFBR-709DMZ-IN2

Third Party Issues/Limitations:

1. Terminal switching results in hard hang randomly. Issue root caused gnome which is third party component.
<https://bugs.launchpad.net/ubuntu/+source/gdm3/+bug/1758512> .
2. Switching to console mode upon hotplug results in soft hang. Issue root caused gnome which is third party component.
<https://bugs.launchpad.net/ubuntu/+source/gdm3/+bug/1758512> .

3. Stutter can be observed when stream framerate and monitor refresh rate are different. This is expected phenomenon. Stutter can be minimized with interpolation option in mpv. But it can introduce corruption and other side effects.

Troubleshooting

The user-space components are selected with the best possible availability of stable components at the time of release.

The user-space components are available to the users through open source policy. Please be advised to upgrade the open source user-space components as per need and resolution through latest user-space.

The Embedded release for open source component is based on Ubuntu 18.04.1 distribution.

Here are a few troubleshoot pointers for resolution for non-amdgpu components.

1. In multi-GPU use-case, a monitor connected to APU doesn't come up while boot during multiscreen rendering. The monitor connect to dGPU loads correctly.
This issue happens because of gnome desktop environment used by 18.04.1. The gnome desktop environment does not support multi-screen configuration. To fix this issue, use XFCE desktop environment.
2. dmesg points to "Bandwidth validation fails", one of the monitors gets blackout after connecting more than 2 - 4K monitors on MF
When display load fails the bandwidth validation, there is no fallback mechanism provided through the Linux OS. Under such situation, customers can reduce the refresh rates or resolution of monitor for the getting the monitor lightup.
3. Unigine Heaven Pro shows white screen
Follow the following steps to allow GLSL #extension directives in the middle of shaders

1. Install driconf (sudo apt-get install driconf)
2. Run driconf (sudo driconf)
3. In application settings add Unigine heaven if it does not exist (application name: Unigine Heaven, Executable name: heaven_x64)
4. Add: Allow GLSL #extension directives in the middle of shaders: Yes (using "add setting" button. You can remove all other settings if present)
5. Retry unigine heaven

4. Suspend/Resume with and without playback
Use systemctl suspend rather than pm-suspend.

Below link suggests the usage of systemctl suspend.

<https://askubuntu.com/questions/1792/how-can-i-suspend-hibernate-from-command-line>

More details on why systemd is preferred over other tools

<https://wiki.archlinux.org/index.php/Systemd>

Chapter 11 **Support**

Please contact your Field Applications Engineer for support on this release.